

610189/01

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition	Errors
1	IS&R	L1	4989	(385/31,49,14,36).CCLS.	US-PGPUB; USPAT	2005/07/09 13:03			
2	BRS	L2	4260	(mirror or mirrored or reflector or reflective or deflector) with ("45" or "54.7" or "54.74" or "70.5" or "70.53") with (degree or degrees)	US-PGPUB; USPAT	2005/07/09 15:28			
3	BRS	L3	115	L1 and L2	US-PGPUB; USPAT	2005/07/09 13:03			
4	BRS	L4	40	L2 same (pyramid or pyramidal)	US-PGPUB; USPAT	2005/07/09 13:03			
5	BRS	L5	55	L2 with (gold or au or multilayer or multilayered or multi-layer or multilayered)	US-PGPUB; USPAT	2005/07/09 13:03			
6	BRS	L6	155	L2 same (fiber or waveguide) same (pd or photodiode or photodetector or ld or laser or vcsel)	US-PGPUB; USPAT	2005/07/09 13:03			
7	BRS	L7	113	L6 not (L3 or L4 or L5)	US-PGPUB; USPAT	2005/07/09 13:05			
8	BRS	L10	167	((mirror or mirrored or reflector or reflective or deflector) with (pyramid or pyramidal or triangular)) and "385"/\$.ccls.	US-PGPUB; USPAT	2005/07/09 15:42			
9	BRS	L11	158	10 not (3 or 4 or 6 or 7)	US-PGPUB; USPAT	2005/07/09 15:53			